CERTIFICATE OF CALIBRATION

ISSUED BY EURO PRODUCTS CALIBRATION LABORATORY DATE OF ISSUE july 18, 2005



0496

6
EURO PRODUCTS LIMITED



Yardley House, Yardley Street, Stourbridge, West Midlands DY9 7 AT

Tel: (01384) 895000 Fax: (01384) 897000

E-mail: sales@europroducts.co.uk Website: www.europroducts.co.uk PAGE 1 OF 1 PAGES

APPROVED SIGNATORY

D. Perkins

T. Chandler

C. Perkins

Client:

Impacta Instrumentos

Padrão: I 013

Validade: Indeterminado

Description:

Rockwell Reference Hardness Tester Block

Block Serial Number:

5834

1013

Date of Calibration:

july 18, 2005

Calibration Details:

The above Reference Hardness Block has benn examined in the EURO PRODUCTS calibration laboratory and was found to comply with the requirements of BS EN ISO 6508-3 1999 clause 3 and ASTM E 18:2000 clause 16. The above Reference Hardness Block value was calibrated on a standardising machine complying with the requirements of BS EN ISO 6508-3 and ASTM E 18: 2000, having hardness scales traceable to the UK National Scales as defined by IMGC: the machine was also indirectly verified in the rockwell c scale with reference blocks calibrated by

NIST

Results:

The above reference Hardness Block was found to cumply with the requirements of BS EN ISO 6508-3 clause 7 and ASTM E 18:2000 clause 20 and the hardness values obtained are given

below:

Mean Hardness Value:	HRC 32.1	Uniformity of Hardness: 0.4 units
Maximum Value : Test 1:	HRC 32.6	Test 2: HRC 32.7 Test 4: HRC 31.6
Minimum Vallue : Test 3 :	HRC 31.6	

Calibration made at:

23ºC + 2

Reference Hardness Block Thikness:

12,2 mm

Uncertainty of Measurem

+ 1 HRC

Approved Signatory:

Validity:

Hardness Reference Block is only valid for the scale for wich it was calibrated. It is recommended that the duration of the calibration validity should be limited to 5 years.

The reported expanded uncertainty is based on a standard uncertainty multiplied by a coverage factor k=2, providing a level of confidence of approximately 95%. The uncertainty evaluation has been carried out in accordance with UKAS requirements.

This certificate is issued in accordance with the laboratory accreditation requirements of the United Kingdom Accreditation Service. It provides tracability of measurement to recognised national standards, and to units of measurement realised at the National Physical Laboratory or other recognised national standards laboratories. This certificate may not be reproduced other than in full, except with the prior written approval of the issuing laboratory